

Boomlift / Manlift

Used Boom Lift Ventura - The boom lift is one of the most popular kinds of aerial machinery. Also referred to as elevating work platforms, aerial devices, cherry pickers, mobile elevating work platforms and aerial work platforms, boom lifts are capable of completing jobs at higher elevations easily and efficiently. Many industries rely on boom lifts every day including retail locations, construction contractors, companies and warehouses. Staying safe while working at high altitude is essential for daily success. There is a wide variety of boom lift models to choose from. A single operator can control a variety of boom lift models. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. Ladders need to be secured on solid, even ground in order to be safely accessible, making them hard to rely on in a natural orchard setting. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Boom lifts make working over top of obstacle much easier as many models have been engineered to travel up and over items. Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. Articulated boom lifts are comprised of many joints that allow the machine to bend under or over obstacles. To enable operators to access many places, these sections of the boom lift can move independently. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. There are articulating boom lifts complete with an additional jib that allows the platform to extend an extra 6 feet in any direction. Since these machines commonly work on steep ground and rough terrain, they resemble "spiders" with their long legs, and often go by that nickname on the job site. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Certain larger units feature a jib located at the top that looks similar to an articulating boom lift model. Some models of boom lifts can achieve a reach of more than 180 feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. With 4WD options and their capacity to travel through small spaces, boom lifts are used in a variety of industries. In terms of combining height and reach, telescopic boom lifts are your best bet. Jib The jib is the extension found at the end of the main boom and between the platform. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Articulating boom lifts and telescoping boom lifts may have jibs. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. This model features excellent mobility and is capable of accessing hard to reach areas. The machine can lift up, over and out with ease, making difficult locations easy to work with. In 1985, the first Genie Z-30/20 articulating Z-boom was introduced; their up-and-over capacity make them instantly popular and this design continues

today. Proper Safety Measures Safety is the utmost priority when operating any kind of boom lift. All known safety hazards must be known to anyone working within the vicinity. Safely operating the equipment is a top priority for the operator and everyone in the working environment. Proper safety gear and communication need to be completed prior to operating. Be aware of any battery gases, engine fuels, combustible items, lit cigarettes or open flames near the machine and do not operate if any flammable or combustible items are present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance Daily maintenance includes a visual inspection and consulting the maintenance manual to ensure the machine is up to date and will operate safely. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. Typically the wide umbrella of maintenance is distinguished by subsections such as Commissioning and Programmed Maintenance Intervals, Annual Maintenance, and Quarterly Maintenance. Maintenance Inspection Report The boom lift components are divided and categorized to streamline the process of inspection. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Improper completion can result in unsafe operation, damage to components, poor performance and downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. Quarterly and annual maintenance is required to be performed throughout the year. Programmed maintenance procedures are completed based on machine operating hours or during "pre-delivery" preparation. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.